



AUTOGEAR OIL MTF 70W

Product Description:

AUTOGEAR OIL MTF 70W is a high quality fully synthetic manual transmission fluid designed for passenger- and light commercial vehicles using both manual and dry-DCT transmissions and transaxles. Not suitable for differentials and other API: GL-5 applications.

AUTOGEAR OIL MTF 70W is based on high quality fully synthetic base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Superior low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

AUTOGEAR OIL MTF 70W is recommended for the following specifications:

API: GL-4	BMW MTF LT-3	Ford WSD-M2C200-D2	GM W16612
GM 1940004	GM 19259104	PSA B71 2316	PSA 9730 A8
Renault DC4 DW5	NFX	VW G 052 178	VW G 052 512
VW G 052 527	VW G 052 549	VW G 052 726	VW G 060 726
VW G 070 726	Fiat MZ7		

AUTOGEAR OIL MTF 70W is suitable for use where the following OEM products are demanded:

BOT 303 BOT 350M3 HBVFE Hyundai / KIA MTF & DCTF



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	70W
Density@15°C	kg/m ³	ASTM D4052	842
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	26.4
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.4
Brookfield Viscosity @-40°C	cP	ASTM D2983	38000
Viscosity Index		ASTM D2270	145
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-69

Product Nr: 43381
Date Superseded: -

Date Issued: 23-03-2023
Revision nr: -