

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : 43120 - AUTOGEAR OIL LS 80W-90  
Product code : 43120

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Function or use category : Lubricants and additives

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

77 Lubricants B.V.  
NL- 1761 JA  
The Netherlands  
T +31 (0)78 6527652  
[technical@77lubricants.nl](mailto:technical@77lubricants.nl) - [www.77lubricants.nl](http://www.77lubricants.nl)

**1.4. Emergency telephone number**

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazardous to the aquatic environment – Chronic Hazard, H412  
Category 3  
Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Signal word (CLP) : -  
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.  
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read carefully and follow all instructions.  
P273 - Avoid release to the environment.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Residual oils (petroleum), solvent-dewaxed substance with national workplace exposure limit(s) (NL)	CAS-No.: 64742-62-7 EC-No.: 265-166-0 EC Index-No.: 649-471-00-X REACH-no: 01-2119480472-38	$\geq 55 - < 75$	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	$\geq 25 - < 45$	Not classified
Polysulphides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3	$\geq 1 - < 3$	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Amines, C10-14-tert-alkyl	EC-No.: 701-175-2 REACH-no: 01-2119456798-18	$\geq 0.1 - < 1$	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:vapour), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	$< 0.3$	Not classified
Distillates (petroleum), solvent-refined heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64741-88-4 EC-No.: 265-090-8 EC Index-No.: 649-454-00-7 REACH-no: 01-2119488706-23	$< 0.3$	Not classified

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Polysulphides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3	(46 ≤ C < 100) Skin Sens. 1B, H317
Amines, C10-14-tert-alkyl	EC-No.: 701-175-2 REACH-no: 01-2119456798-18	(6.7 ≤ C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid spilling the product, as this might cause falls.
------------------	--

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

### 6.2. Environmental precautions

Avoid release to the environment.

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes.
Handling temperature	: ≤ 40 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Provide local exhaust or general room ventilation.
Storage conditions	: Store in a well-ventilated place. Keep cool.
Storage temperature	: ≤ 40 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Keep only in original container. Store in a closed container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5 mg/m <sup>3</sup>
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup>
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5 mg/m <sup>3</sup>

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

IOEL STEL	10 mg/m <sup>3</sup>
-----------	----------------------

#### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup>

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

##### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.35		EN ISO 374

##### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown. amber.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -33 °C (ASTM D7346)
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 200 °C (ASTM D92)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 131 mm <sup>2</sup> /s @ 40°C (ASTM D7042)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 887 kg/m <sup>3</sup> @ 15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong oxidizing agents.

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Residual oils (petroleum), solvent-dewaxed (64742-62-7)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rat)	> 2000 mg/kg

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 2000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (mg/l)	> 5000 mg/l/4h
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Polysulphides, di-tert-Bu (68937-96-2)

LD50 oral (rat)	> 2000 mg/kg
LD50 dermal (rat)	> 2000 mg/kg

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (mg/l)	> 5000 mg/m <sup>3</sup>
LC50 inhalation (rat) (Vapours - mg/l/4h)	5.53 mg/l/4h

#### Amines, C10-14-tert-alkyl

LD50 oral (rat)	612 mg/kg (OECD 401)
LD50 dermal (rat)	251 mg/kg (OECD 402)
LC50 inhalation (rat) (Vapours - mg/l/4h)	1.19 mg/l/4h (OECD 403)

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
----------------------------	---

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
Aspiration hazard	: Not classified
<b>43120 - AUTOGEAR OIL LS 80W-90</b>	
Viscosity, kinematic	131 mm <sup>2</sup> /s @ 40°C (ASTM D7042)
<b>Residual oils (petroleum), solvent-dewaxed (64742-62-7)</b>	
Viscosity, kinematic	490 mm <sup>2</sup> /s @40°C
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	98 (98 – 108) mm <sup>2</sup> /s @40°C
<b>Polysulphides, di-tert-Bu (68937-96-2)</b>	
Viscosity, kinematic	716.19 mm <sup>2</sup> /s @20°C
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Viscosity, kinematic	150 (1.99 – 847) mm <sup>2</sup> /s @40°C
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
Viscosity, kinematic	28.51 mm <sup>2</sup> /s @40°C
<b>Amines, C10-14-tert-alkyl</b>	
Viscosity, kinematic	3.44 mm <sup>2</sup> /s

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Polysulphides, di-tert-Bu (68937-96-2)</b>	
EC50 - Crustacea [1]	63 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l
NOEC chronic algae	0.696 mg/l



# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	> 10 mg/l Daphnia magna (21d)
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h)

<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)

<b>Amines, C10-14-tert-alkyl</b>	
LC50 - Fish [1]	1.3 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	2.5 mg/l Daphnia magna
EC50 72h - Algae [1]	0.44 mg/l Pseudokirchneriella subcapitata
NOEC (chronic)	0.078 mg/l
NOEC chronic fish	0.078 mg/l Oncorhynchus mykiss (96d)
NOEC chronic algae	0.05 mg/l Pseudokirchneriella subcapitata (72h)

### 12.2. Persistence and degradability

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD TG 301 F (28d)

<b>Polysulphides, di-tert-Bu (68937-96-2)</b>	
Biodegradation	13 % OECD TG 301 B (28d)

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Biodegradation	31 % OECD 301F (28d)

<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD 301F (28d)

<b>Amines, C10-14-tert-alkyl</b>	
Biodegradation	21.8 % OECD 301D (28d)

### 12.3. Bioaccumulative potential

<b>Residual oils (petroleum), solvent-dewaxed (64742-62-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	> 3.5

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Polysulphides, di-tert-Bu (68937-96-2)	
Bioconcentration factor (BCF REACH)	188
Partition coefficient n-octanol/water (Log Kow)	6
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Bioconcentration factor (BCF REACH)	260
Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6
Amines, C10-14-tert-alkyl	
Partition coefficient n-octanol/water (Log Pow)	2.9 @ 20°C

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW, EC 2000/532)	: 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils
HP Code	: HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on the Canadian DSL (Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
3	Composition/information on ingredients	Modified	

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)

# 43120 - AUTOGEAR OIL LS 80W-90

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

### Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.